


joggers


technical data		R-2	RA-2	R-4	RA-4	RAH-4
table size (y)	[mm in]	720 28.35	720 28.35	900 35.43	900 35.43	900 35.43
table size (x)	[mm in]	870 34.25	870 34.25	1,150 45.28	1,150 45.28	1,150 45.28
format size min. (y)	[mm in]	—	—	—	—	420 16.54
format size min. (x)	[mm in]	—	—	—	—	570 22.44
pusher size max. (y)	[mm in]	—	—	—	—	750 29.53
pusher size max. (x)	[mm in]	—	—	—	—	1,140 44.88
ream height min.	[mm in]	30 1.18	30 1.18	30 1.18	30 1.18	30 1.18
ream height max. *	[mm in]	165 6.50	165 6.50	165 6.50	165 6.50	140 5.51
table height min.	[mm in]	860 33.86	860 33.86	860 33.86	860 33.86	860 33.86
table height max.	[mm in]	950 37.40	950 37.40	950 37.40	950 37.40	970 38.19
noise level (after EN 13023)	[dB(A)]	79	79	79	79	79
installation data						
width (B)	[mm in]	1,270 50.00	1,270 50.00	1,550 61.02	1,550 61.02	1,605 63.19
depth (A)	[mm in]	790 31.10	1,170 46.06	970 38.19	1,290 50.79	1,565 61.61
height	[mm in]	1,085 42.72	1,875 73.82	1,085 42.72	1,875 73.82	1,875 73.82
weight, net	[kg lbs]	350 772	450 992	420 926	550 1,213	635 1,400
static floor load	[daN/m ² lbs/sqft]	467	303	379	276	257
specific surface pressure	[daN/cm ² lbs/sqin]	7.1	9.2	8.6	11.2	13.0
compressed air @ 6-8 bar	[l/min]	2	9	2	9	25
voltage supply three phase 200-240 V, 50/60 Hz						
power consumption	[A]	3.1	3.1	3.1	3.5	3.5
fusing max	[A]	15	15	15	15	15
voltage supply three phase 360-420 V, 50/60 Hz						
power consumption	[A]	1.5	1.5	1.5	1.7	1.7
fusing max	[A]	16	16	16	16	16
electrical power input (apparent power)	[kVA]	0.9	0.9	0.9	1	1
power output (thermal rating)	[kW]	0.9	0.9	0.9	1	1
power output (thermal rating)	[BTU]	3,072	3,072	3,072	3,413	3,413



Subject to technical alterations.

joggers

technical data		R-6	RA-6	RAH-6	RA-7S
table size (y)	[mm in]	1,130 44.49	1,130 44.49	1,130 44.49	1,260 49.61
table size (x)	[mm in]	1,450 57.09	1,450 57.09	1,450 57.09	1,650 64.96
format size min. (y)	[mm in]	—	—	—	—
format size min. (x)	[mm in]	—	—	—	—
pusher size max. (y)	[mm in]	—	—	1,000 39.37	—
pusher size max. (x)	[mm in]	—	—	1,440 56.69	—
ream height min.	[mm in]	30 1.18	30 1.18	30 1.18	10 0.39
ream height max. *	[mm in]	165 6.50	165 6.50	140 5.51	165 6.50
table height min.	[mm in]	890 35.04	890 35.04	890 35.04	880 34.65
table height max.	[mm in]	980 38.58	980 38.58	980 38.58	980 38.58
noise level (after EN 13023)	[dB(A)]	81.5	81.5	81,5	81.5
installation data					
width (B)	[mm in]	1,850 72.83	1,850 72.83	1,955 76.97	2,080 81.89
depth (A)	[mm in]	1,200 47.24	1,570 61.81	1,800 70.87	2,180 85.83
height	[mm in]	1,085 42.72	1,875 73.82	1,875 73.82	1,700 66.93
weight, net	[kg lbs]	520 1,146	730 1,609	800 1,764	1,100 2,425
static floor load	[daN/m ² lbs/sqft]	241	248	228	245
specific surface pressure	[daN/cm ² lbs/sqin]	10.6	14.7	16.3	21.8
compressed air @ 6-8 bar	[l/min]	3	13	29	20
voltage supply three phase 200-240 V, 50/60 Hz					
power consumption	[A]	3.1	3.5	3.5	7.3
fusing max	[A]	15	15	15	16
voltage supply three phase 360-420 V, 50/60 Hz					
power consumption	[A]	1.5	1.7	1.7	3.5
fusing max	[A]	16	16	16	16
electrical power input (apparent power)	[kVA]	1	1	1	2
power output (thermal rating)	[kW]	1	1	1	2
power output (thermal rating)	[BTU]	3,413	3,413	3,413	6,826



Subject to technical alterations.