

stack lifts

technical data		S-3		S-6	
pallet size max. (y)	[mm in]	800	31.4961	1,050	41.3386
pallet size max. (x)	[mm in]	1,200	47.2441	1,450	57.0866
usable fork length	[mm in]	900	35.4331	1,100	43.3071
platform size max. (y)	[mm in]	—	—	—	—
platform size max. (x)	[mm in]	—	—	—	—
stroke max.	[mm in]	880	34.6457	880	34.6457
carrying capacity max.	[mm in]	1,000	2,205	1,000	2,205
noise level (after DIN 45635)	[dB]	< 70		< 70	

S-FA-3		S-FA-6	
800	31.4961	1,050	41.3386
1,200	47.2441	1,450	57.0866
900	35.4331	1,100	43.3071
—	—	—	—
—	—	—	—
880	34.6457	880	34.6457
1,000	2,205	1,000	2,205
< 70		< 70	

LW 450-1		LW 1000-4		LW 1000-6	
620	24.4094	800	31.4961	1,050	41.3386
840	33.0709	1,200	47.2441	1,450	57.0866
—	—	—	—	—	—
620	24.4094	840	33.0709	1,090	42.9134
840	33.0709	1,270	50.0000	1,520	59.8425
850	33.4646	850	33.4646	850	33.4646
450	992	1,000	2,205	1,000	2,205
77,9		77,9		77,9	

technical details are subject to change.

