

Transomat TRE

technical data		TRE 90-4	TRE 130-4	TRE 130-5	TRE 160-6	TRE 160-7S
format min. (y)	[mm in]	400 15.75	400 15.75	400 15.75	500 19.69	650 25.59
format min. (x)	[mm in]	400 15.75	400 15.75	400 15.75	400 15.75	450 17.72
format max. (y)	[mm in]	800 31.50	800 31.50	950 37.40	1,050 41.34	1,220 48.03
format max. (x)	[mm in]	1,200 47.24	1,200 47.24	1,260 49.61	1,450 57.09	1,640 64.57
label size min. (y)	[mm in]	105 4.13	105 4.13	105 4.13	105 4.13	105 4.13
label size min. (x)	[mm in]	148 5.83	148 5.83	148 5.83	148 5.83	148 5.83
height of ream min. (fully automatic)	[mm in]	40 1.57	40 1.57	40 1.57	40 1.57	40 1.57
height of ream max.	[mm in]	165 6.50	165 6.50	165 6.50	165 6.50	165 6.50
height of pile max. (+ 1 ream)	[mm in]	850 33.46	1,300 51.18	1,300 51.18	1,600 62.99	1,600 62.99
carrying capacity max.	[kg lbs]	200 441	200 441	200 441	300 661	300 661
time for unloading min.	[sec]	30	18	18	22	23
time for unloading max.	[sec]	40	30	30	37	38
noise level (after EN 13023)	[dB(A)]	< 70	< 70	< 70	< 70	< 70
installation data						
width (B)	[mm in]	2,900 114.17	3,250 127.95	3,400 133.86	4,000 157.48	4,700 185.04
depth (A)	[mm in]	1,550 61.02	1,550 61.02	1,700 66.93	2,180 85.83	2,350 92.52
height	[mm in]	2,000 78.74	2,400 94.49	2,400 94.49	2,800 110.24	2,900 114.17
weight, net	[kg lbs]	890 1,962	900 1,984	950 2,094	1,900 4,189	2,000 4,409
compressed air @ 6-8 bar	[l/min]	8	7	7	10	14
voltage supply three phase 200-240 V, 50/60 Hz						
power consumption	[A]	2	3.3	2	5	5.8
fusing max	[A]	15	15	15	15	15
voltage supply three phase 360-420 V, 50/60 Hz						
power consumption	[A]	2	1.6	2	2.4	2.8
fusing max	[A]	16	16	16	16	16
electrical power input (apparent power)	[kVA]	2.5	1.2	2.5	1.6	1.8
power output (thermal rating)	[kW]	2.5	1.2	2.5	1.6	1.8
power output (thermal rating)	[BTU]	8,533	4,096	8,533	5,461	6,143

² data are not available

Subject to technical alterations.

