


stack lifts


technical data		LW 450-2	LW 1000-4	LW 1200-4	LW 1200-6	LW 2000-6	LW 2000-7S
inside dimension platform max. (y)	[mm in]	620 24.41	840 33.07	840 33.07	1,090 42.91	1,090 42.91	1,240 48.82
inside dimension platform max. (x)	[mm in]	900 35.43	1,270 50.00	1,270 50.00	1,520 59.84	1,520 59.84	1,790 70.47
stroke max	[mm in]	850 33.46	850 33.46	850 33.46	850 33.46	900 35.43	900 35.43
carrying capacity max	[mm in]	450 992	1,000 2,205	1,200 2,646	1,200 2,646	2,000 4,409	2,000 4,409
noise level (after EN 13023)	[dB(A)]	77,9	77,9	77,9	77,9	77,9	77,9
installation data							
width (B)	[mm in]	1,190 46.85	1,500 59.06	1,560 61.42	1,820 71.65	1,850 72.83	2,023 79.65
depth (A)	[mm in]	1,045 41.14	1,275 50.20	1,275 50.20	1,550 61.02	1,590 62.60	1,740 68.50
height	[mm in]	1,500 59.06	1,500 59.06	1,500 59.06	1,500 59.06	1,640 64.57	1,640 64.57
height (at max. stroke)	[mm in]	1,960 77.17	1,960 77.17	1,960 77.17	1,960 77.17	2,120 83.46	2,120 83.46
weight, net	[kg lbs]	450 992	550 1,213	570 1,257	700 1,543	1,150 2,535	1,200 2,646
voltage supply three phase 200-240 V, 50/60 Hz							
power consumption	[A]	0.2	0.4	0.4	²	²	²
fusing max	[A]	10	10	10	10	10	10
voltage supply three phase 360-420 V, 50/60 Hz							
power consumption	[A]	0.1	0.2	0.2	²	²	²
fusing max	[A]	10	10	10	10	10	10
electrical power input (apparent power)	[kVA]	0.75	0.75	0.75	0.75	1.5	1.5
power output (thermal rating)	[kW]	0.75	0.75	0.75	0.75	1.5	1.5
power output (thermal rating)	[BTU]	2,560	2,560	2,560	2,560	5,120	5,120



technical data		S-3	S-6
pallet size max. (y)	[mm in]	800 31.50	1,050 41.34
pallet size max. (x)	[mm in]	1,200 47.24	1,450 57.09
usable fork length	[mm in]	900 35.43	1,100 43.31
stroke max	[mm in]	880 34.65	880 34.65
carrying capacity max	[mm in]	1,000 2,205	1,000 2,205
noise level (after EN 13023)	[dB(A)]	< 70	< 70
installation data			
width (B)	[mm in]	see machine floorplan	
depth (A)	[mm in]	see machine floorplan	
height	[mm in]	—	—
height (at max. stroke)	[mm in]	—	—
weight, net	[kg lbs]	200	200
voltage supply three phase 200-240 V, 50/60 Hz			
power consumption	[A]	feed-in from cutter	
fusing max	[A]	—	—
voltage supply three phase 200-240 V, 50/60 Hz			
power consumption	[A]	feed-in from cutter	
fusing max	[A]	—	—
electrical power input (apparent power)	[kVA]		
power output (thermal rating)	[kW]		
power output (thermal rating)	[BTU]		

² data are not available

S-FA-3		S-FA-6	
800 31.50	1,050 41.34		
1,200 47.24	1,450 57.09		
900 35.43	1,100 43.31		
880 34.65	880 34.65		
1,000 2,205	1,000 2,205		
< 70	< 70		
900 35.43	1,150 45.28		
1,865 73.43	2,055 80.91		
1,911 75.24	1,911 75.24		
²	²		
320 705	340 750		
0.15	0.15		
10	10		
0.15	0.3		
10	10		
²	0.15		
²	0.15		
²	511.95		



technical details are subject to change.